

## FINAFOG-PP200

DESCRIPTION	:	Antifog additive for Polypropylene		opylene
SPECIFICATIONS	:	Appearance	:	Creamish powder
		Melting point	:	45 <u>+</u> 5°C

(Slight variations in the specifications stated due to raw materials and production conditions are possible though they have no influence on the application properties described.)

<u>APPLICATIONS</u>	:	<ul> <li>Antifog agent for food wrapping / agricultural films like green houses, large domes, small tunnels etc.</li> </ul>
PROPERTIES	:	- FinaFog-PP200 acts as an antifog additive for PP film
		<ul> <li>It converts water droplets formed on the film into a continuous transparent water layer</li> </ul>
		<ul> <li>Performance of PP films does not get affected due to the addition of FinaFog-PP200</li> </ul>
		- Suitable for Cold & Hot fog applications
<u>USE LEVEL</u>	:	1- 5% depending upon the requirement.
<u>STORAGE</u>	:	Shelf-life is up to one year from the date of manufacture if stored under recommended storage conditions (cool & dry storage)
		Due to its lower melting point, it may form agglomerates during transit or storage

The recommendations in this bulletin are made without guarantee since the conditions of use are beyond our control. Users should make their own tests depending on machinery available and desired properties.